

FCOB Flood Light Uranus Series

High brightness/high lightning protection and surge resistance/IP66 waterproof



IP66



Features

- Ultra thin lamp body design for easy installation and transportation.
- Multiple waterproof design, IP66 strong waterproof, and strong environmental adaptability.
- Unique chip packaging technology with low thermal resistance and high light efficiency.
- Die cast aluminum heat sink for strong air convection heat dissipation.

Basic Parameters

Model	Size	Wattage	Input Voltag	CCT	Beam Angle	CRI	Colour	PF
FCOB-30W	φ165*1128*26mm	30W	200-240V	3000K/6000K	115°	Ra ≥ 80	Black	≥0.97
FCOB-50W	φ185*160*26mm	50W	200-240V	3000K/6000K	115°	Ra ≥ 80	Black	≥0.97
FCOB-100W	φ262*210*26mm	100W	200-240V	3000K/6000K	115°	Ra ≥ 80	Black	≥0.97
FCOB-150W	φ283*239*26mm	150W	200-240V	3000K/6000K	115°	Ra ≥ 80	Black	≥0.97
FCOB-200W	φ33*26.5*31mm	200W	200-240V	3000K/6000K	115°	Ra ≥ 80	Black	≥0.97

Multi-scenario Application

